according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 661-209-0004 UV SEALER

Print date: 08.10.2020 Revision date: 04.12.2019 EN Version: 2.0 Issue date: 04.12.2019 Page 1 / 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) 661-209-0004
Identification of the substance or mixture UV SEALER
COLOURLESS

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor):

Teknos (M) Sdn. Bhd.

PLO 577, Jalan Keluli 8 Telephone: +60 7 251 5115 Kawasan Perindustrian Pasir Gudang Telefax: +60 7 251 3115

81700 Pasir Gudang, Johor, Malaysia **Dept. responsible for information:**

Laboratory

E-mail: prod-safe@teknos.com

1.4. Emergency telephone number

Emergency telephone: +60 7 251 5115

Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Skin Irrit. 2 / H315 skin corrosion/irritation Causes skin irritation.

Eye Dam. 1 / H318 Serious eye damage/eye irritation

Skin Sens. 1 / H317 Respiratory or skin sensitisation

Skin corrosion/irritation

Causes skin irritation.

Causes skin irritation.

May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Danger

Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves and eye/face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P501 Dispose of contents/container to industrial incineration plant.

contains:

DPGDA

Polyamine amide salt

Supplemental Hazard information (EU)

not applicable

2.3. Other hazards

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Product description / chemical characterization

Description UV liquid

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 661-209-0004 UV SEALER

 Print date:
 08.10.2020
 Revision date: 04.12.2019
 EN

 Version:
 2.0
 Issue date: 04.12.2019
 Page 2 / 7

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification: // Remark	Wt %
260-754-3 57472-68-1	DPGDA Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Skin Sens. 1 H317	12.5 - 20
204-337-6 119-61-9	BENZOPHENON STOT RE 2 H373 / Aquatic Chronic 2 H411	1 - 2.5
213-426-9 947-19-3	Photoinitiator Acute Tox. 5 H303 / Aquatic Acute 3 H402	1 - 2.5
	Polyamine amide salt Flam. Liq. 3 H226 / Skin Sens. 1 H317 / STOT SE 3 H336 / Aquatic Chronic 3 H412	< 0.5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners. Conditions to avoid: UV-radiation/sunlight Causes mild skin irritation.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 661-209-0004 UV SEALER

Print date: 08.10.2020 Revision date: 04.12.2019 EN Version: 2.0 Revision date: 04.12.2019 Page 3 / 7

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

Persons with a history of skin sensitisation problems should not be employed in any process in which this product is used.

7.1. Precautions for safe handling

Advices on safe handling

Use only in well-ventilated areas. Keep away from heat sources, sparks and open flames. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Keep only in the original container.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used:

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



661-209-0004 Article No.: **UV SEALER**

Print date: 08.10.2020 Revision date: 04.12.2019 Version: Issue date: 04.12.2019

Thickness of the glove material > 0.4 mm; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eve protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance:

Physical state: Colour: refer to label Odour: characteristic **Odour threshold:** not determined pH at 25 °C:: not determined Melting point/freezing point: not determined Initial boiling point and boiling range: not determined

Flash point: > 70 °C

Method: DIN 53213

Evaporation rate: not determined

Flammability (solid, gas):

not determined Burning time (s):

Upper/lower flammability or explosive limits:

Lower explosion limit: not determined **Upper explosion limit:** not determined Vapour pressure at 25 °C:: not determined not determined Vapour density:

Relative density:

Density at 25 °C:: 1.20 g/cm³

Solubility(ies):

insoluble Water solubility (g/L) at 20 °C:: Partition coefficient: n-octanol/water: see section 12 not determined **Auto-ignition temperature: Decomposition temperature:** not determined Viscosity at 25 °C:: > 54 s 6 mm Method: DIN 53211

not applicable

Explosive properties: Oxidising properties: not applicable

9.2. Other information

Solid content (%): 99.00 Wt %

solvent content:

1.00 Wt % Organic solvents: Water: 0.00 Wt %

Solvent separation test (%): < 3 Wt % (ADR/RID)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 661-209-0004 UV SEALER

Print date: 08.10.2020 Revision date: 04.12.2019 EN Version: 2.0 Revision date: 04.12.2019 Page 5 / 7

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

This preparation contains material instable under the following conditions: Heat, strong ultraviolet radiation. An exotherm polymerization of the product may thereby be caused. Avoid unintended contact with it. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

DPGDA

oral, LD50, Rat

skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Polyamine amide salt

Skin:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Toxicological data are not available.

Specific target organ toxicity

Polyamine amide salt

Specific target organ toxicity (single exposure), drowsiness

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

The fractions of acrylic resin in the preparation have an irritant effect. Prolonged or repeated contact with the preparation can lead to irritations of mucous membranes and of skin such as redness, formation of blebs, dermatitis, etc.. Cases of allergic skin reactions have been observed. Liquid splashes can lead to irritations of the eyes. Inhaling of drolets in the air or aerosols may lead to irritations of the respiratory tract. Ingestion may cause nausea, weakness and affect the central nervous system.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 661-209-0004 UV SEALER

Print date: 08.10.2020 Revision date: 04.12.2019 EN Version: 2.0 Revision date: 04.12.2019 Page 6 / 7

12.1. Toxicity

No information available.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* waste paint and varnish containing organic solvents or

other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable
Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code -

Sea transport (IMDG)

EmS-No. not applicable

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 661-209-0004 UV SEALER

 Print date:
 08.10.2020
 Revision date: 04.12.2019
 EN

 Version:
 2.0
 Issue date: 04.12.2019
 Page 7 / 7

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 141.690

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Skin Irrit. 2 / H315

Eye Dam. 1 / H318

Skin corrosion/irritation

Serious eye damage/eye irritation

Skin Sens. 1 / H317

STOT RE 2 / H373

Skin corrosion/irritation

Serious eye damage/eye irritation

Respiratory or skin sensitisation

Specific target organ toxicity (repeated exposure)

Skin Corrosion/irritation

Causes skin irritation.

Causes skin irritation.

May cause an allergic skin reaction.

May cause damage to organs (or state all organs affected, if known) through prolonged or

organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of

exposure cause the hazard).

Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.

Acute Tox. 5 / H303 Acute toxicity (oral) May be harmful if swallowed.

Aquatic Acute 3 / H402 Hazardous to the aquatic environment Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour.

STOT SE 3 / H336 Specific target organ toxicity (single May cause drowsiness or dizziness.

exposure)

Aquatic Chronic 3 / H412 Hazardous to the aquatic environment Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.