TEKNOS (M) Sdn. Bhd. (formerly known as Teknos Treffert (M) Sdn.

Bhd.)

PLO 577, Jalan Keluli 8 Kawasan Perindustrian Pasir Gudang 81700 Pasir Gudang, Johor, Malaysia

T+60 7 251 5115 F +60 7 251 4115 info.malaysia@teknos.com www.teknos.my



TECHNICAL DATASHEET

Page: 1 / 2

Description : UV PIGMENT PASTE - YELLOW

Product Number : 581047

Description : UV yellow pigment paste is suitable for matching and staining in

> Teknos UV clear base stain and other UV products. It gives and shows good colour stability and compatibility with the right use and

amount.

Characteristics

Viscosity : 1 - 6 dPa.s in Dynamic measurement (#2) at 25°C.

Density $1.09 \pm 0.2 \text{ kg/l}$

Solid Content : 57 - 63%

VOC 36%

Pigments Does not contain any lead, cadmium or chromate.

Application

: Stir well and check before use. Preparation

Hardener : Not required Thinner Not required **Viscosity** As delivered

Storage

Shelf Life 6 months

Conditions Protect from sunlight and frost.

To be stored at 5 - 35°C.

Delivery

Packaging : Available in 20 kg pails.

Delivery Time : Please allow 6 working days of production and transportation.

The information in this datasheet is given to the best of our ability based on our laboratory results. As we have no control over the quality of substrate nor the application conditions and methods used, we recommend the user to test the product for the purpose required. We are not liable for any compensation nor damages arising due to improper use of our products. The information contained herein is subject to change without further notice. This leaflet is invalid when it is replaced by a newer version. Please ask for the latest version.

TEKNOS (M) Sdn. Bhd. (formerly known as Teknos Treffert (M) Sdn. Bhd.) PLO 577, Jalan Keluli 8 Kawasan Perindustrian Pasir Gudang 81700 Pasir Gudang, Johor, Malaysia

T +60 7 251 5115 F +60 7 251 4115 info.malaysia@teknos.com www.teknos.my



TECHNICAL DATASHEET

Page: 2 / 2

Description : UV PIGMENT PASTE - YELLOW

Product Number : 581047

Quantity : Minimum quantity is 20 kg.

Cleaning : Use solvent such as butyl acetate for cleaning.

Precautions : Refer to Safety Data Sheet.

Health & Safety : Refer to Safety Data Sheet.