

TECHNICAL DATASHEET

Description : **UV PIGMENT PASTE - RED**

Product Number : **581048**

Description : UV red pigment paste is suitable for matching and staining in Teknos UV clear base stain and other UV products. It gives and shows good colour stability and compatibility with the right use and amount.

Characteristics

Viscosity : 8 - 13 dPa.s in Dynamic measurement (#2) at 25°C.

Density : 1.12 ± 0.2 kg/l

Solid Content : 56 - 62%

VOC : Max 34%

Pigments : Does not contain any lead, cadmium or chromate.

Application

Preparation : Stir well and check before use.

Hardener : Not required

Thinner : Not required

Viscosity : As delivered

Storage

Shelf Life : 6 months

Conditions : Protect from sunlight and frost.
To be stored at 5 - 35°C.

Delivery

Packaging : Available in 20 kg pails.

Delivery Time : Please allow 6 working days of production and transportation.

Quantity : Minimum quantity is 20 kg.

TEKNOS (M) Sdn. Bhd.
(formerly known as Teknos Treffert (M) Sdn.
Bhd.)
PLO 577, Jalan Keluli 8
Kawasan Perindustrian Pasir Gudang
81700 Pasir Gudang, Johor, Malaysia

T +60 7 251 5115
F +60 7 251 4115
info.malaysia@teknos.com
www.teknos.my



TECHNICAL DATASHEET

Page: 2 / 2

- Description** : **UV PIGMENT PASTE - RED**
- Product Number** : **581048**
- Cleaning** : Use solvent such as butyl acetate for cleaning.
- Precautions** : Refer to Safety Data Sheet.
- Health & Safety** : Refer to Safety Data Sheet.

The information in this datasheet is given to the best of our ability based on our laboratory results. As we have no control over the quality of substrate nor the application conditions and methods used, we recommend the user to test the product for the purpose required. We are not liable for any compensation nor damages arising due to improper use of our products. The information contained herein is subject to change without further notice. This leaflet is invalid when it is replaced by a newer version. Please ask for the latest version.