

TECHNICAL DATASHEET

Description : **UVILUX FILLER 237**

Product Number : **611-237-0000**

Description : Colourless acrylated UV-curable filler to be applied by filler machines. The product has excellent sanding, filling and sealing properties and being designs for porous substrates.

Characteristics

Viscosity : 100-130 dPa.s in Dynamic measurement (#2) at 25°C.

Density : 1.23 ± 0.02 kg/l

Solid Content : 98 - 99%

VOC : Max 3%

Classification : Complies with the Environmental Protection Act of 1990.

Application

Preparation : Stir well and check before use.

Hardener : Not required

Thinner : Not required

Viscosity : As delivered

Film Weight : Apply 25 - 40 g/m² (depends on the wood pores).

Mode : Apply in roller machine.

Curing : Semi-cure: 70 - 80 mJ/cm²
Surface cure: 130 - 140 mJ/cm²

Substrate : This product is specially formulated as filler to be applied on WPC or wood substrates with high porosity. Please consult our technical staff prior to other applications.

Storage

TECHNICAL DATASHEET

Description : **UVILUX FILLER 237**

Product Number : **611-237-0000**

Shelf Life : 6 months

Conditions : Protect from sunlight and frost. Keep container tightly closed and in a well ventilated place. Keep away from sources of ignition, heat and oxidizing substances.

To be stored at 5 - 35 °C.

Delivery

Packaging : Available in 20 kg pails.

Delivery Time : Please allow 6 working days of production and transportation.

Cleaning : Use solvent such as butyl acetate for cleaning.

Precautions : Refer to Safety Data Sheet.

Health & Safety : Refer to Safety Data Sheet.