

TECHNICAL DATASHEET

Description : **UV SEALER**
Product Number : **661-209-0004**

Description : Colourless acrylic UV-curable sealer for roller application in the coating process of resistance flooring or PDL board. The UV-sealer shows excellent adhesion, sanding and sealing properties.

Characteristics

Viscosity : 87 sec. in DIN 6mm at 25°C
Density : 1.18 ± 0.02 kg/l
Solid Content : 98 - 99%
VOC : Max 3%
Classification : Complies with the Environmental Protection Act of 1990.

Application

Preparation : Stir well and check before use.
Hardener : Not required
Thinner : Not required
Viscosity : As delivered
Film Weight : Apply 15-20 g/m².
Mode : Apply in roller machine with a shore hardness of offset rollers of 40-50 (Isobutylene / Isoprene-Copolymer or EPDM-Prepolymer).
Curing : Semi cure: 70 - 80 mJ/cm²
Full cure: 200 - 210 mJ/cm²

Substrate : The product is specially formulated as UV sealer to be applied on TEKNOS TREFFERT-COATINGS UV Filler or duro sealer. The product provides excellent support to TEKNOS TREFFERT-Coatings 651-/652 UV- Top coat. Please consult our technical staff prior to other applications.

TECHNICAL DATASHEET

Description : **UV SEALER**
Product Number : **661-209-0004**

Storage

Shelf Life : 6 months
Conditions : Protect from sunlight and frost. Keep container tightly closed and in a well ventilated place. Keep away from sources of ignition, heat and oxidizing substances.

To be stored at 5 - 35 °C.

Delivery

Packaging : Available in 20 kg pails.
Delivery Time : Please allow 6 working days of production and transportation.
Quantity : Minimum quantity is 20 kg.

Cleaning : Use solvent such as butyl acetate for cleaning.

Precautions : Refer to Safety Data Sheet.

Health & Safety : Refer to Safety Data Sheet.